

Line marking machines
SIBEMINI



SIBESTAR S.r.l.

Line marking machines

SIBEMINI



SIBESTAR S.r.l.

TECHNICAL CHARACTERISTICS:

- Petrol motor - 6 Hp - cord starter with automatic rewind – air cooled – silenced – quick starting at all temperatures.
- Compressor - Capacity 280-390 l/min. approx.
- Pressure system with two pressure regulators with manometers, two safety valves and two non-return valves.
- High resistance gun for all types of paint, including reflective road paint.
- Gun start and stop actioned by pneumatic command with button on handle.
- Spray set with manual gun, telescopic
- 24 litre capacity vertical paint tank, incorporated stirrer.
- Working pressure 3 atmospheres.
- 5 litre capacity diluter tank for cleaning spray set.
- Machine's frame constitutes 3,5 litres capacity air reserve.
- Handle with easily-removable controls (to facilitate packing for transportation).
- Box for transporting tools.
- Two front wheels and one rear rotating wheel, with brake.
- Dimensions: 1,40m x 0,85m x 1,00m high.
- Empty weight: Kg 115.
- Supplied with 5m of extension tubing for using with movable gun.
- Suitable for using with all types of paint, including reflective road paint.
- The paint tank can hold a removable container, making it to change colours by simply changing the container, and permitting successive changes of colour ensuring that the colours are not modified.
- Quick "uncoupling" of the motor-compressor from the tank. The motor-compressor, with its wheels, is easy to transport thanks to its limited weight and dimensions. You can easily take it up scaffolding, stairs, pylons and elsewhere on a site, everywhere where you might need compressed air but there's no electric power supply.
- The above-mentioned unit has an outlet to which any spray gun with tank can be attached.

ACCESSORIES AVAILABLE ON REQUEST:

- Additional manual gun.