

Line marking machines

SIBELINE 30 ST



SIBESTAR S.r.l.

SIBELINE 30 ST



SIBESTAR S.r.l.

TECHNICAL CHARACTERISTICS:

- Petrol motor - 6 Hp - cord starter with automatic rewind – air cooled – silenced –
- Quick starting at all temperatures.
- Compressor - Capacity 280-390 l/min. approx.
- Pressure system with two pressure regulators with manometers, two safety valves and two non-return valves.
- High resistance gun for normal and reflective paint.
- Gun start and stop actioned by pneumatic command with button on handle.
- Spray set with manual gun, telescopic. The gun is easily disconnected to facilitate packing and transport.
- 30 litre capacity stainless steel to PED standard paint tank incorporated stirrer.
- Working pressure 4 atmospheres.
- 3.3 litre PED stainless steel air reserve tank
- 3.3 litre capacity PED stainless steel diluter tank for cleaning spray set.
- Two pressure regulators with manometers
- Two certified safety valves
- Pneumatic coupling to regulate air pressure
- Two non-return valves
- Controls on handlebar, easily accessible.
- Box for transporting tools.
- Three wheels (one front and two rear) with air-filled tyres, ball-bearing axles.
- Brake on one of the rear wheels.
- Dimensions: 1,70m x 0,90m x 1,00m high.
- Empty weight: 140 kg approx.
- Supplied with 5m of extension tubing for using with movable gun.
- The equipment is constructed for spraying pre-mixed solvent and water based paints, including reflective and epoxy paints.
- We do no welding on our tanks after they have been tested

DISC UNIT



AUTOMATIC LINE MARKING



SELF-LEVELLING TELESCOPIC UNIT



TROLLEY FOR OPERATOR



20-L ADDITIONAL TANK



SPRAY BOX TO PAINT LINES



ACCESSORIES AVAILABLE ON REQUEST:

- Extra manual gun.
- Extra manual gun with rigid extension.
- Pneumatically-controlled disc unit.
- Pneumo-mechanical automatic line marker.
- Mechanical distance-travelled indicator.
- Additional 20-litre PED stainless steel tank for coloured paints.